

II. AMENDMENTS TO THE CLAIMS

The following listing replaces any and all prior listings of the claims:

1. (Currently amended) A computer-implemented security system for securing an electronic version of a nucleotide chain sequence, comprising:

at least one processing unit;

memory operably associated with the at least one processing unit; and

a security system storable in memory and executable by the at least one processing unit,
the security system comprising:

a system for identifying all coding and non-coding regions in the nucleotide chain sequence;

a system for selectively encrypting the sequence of only the coding regions identified in the nucleotide chain; and

a system for outputting the electronic version of the nucleotide chain sequence, including the encrypted coding regions and the unencrypted non-coding regions, wherein the encrypted coding regions require decryption by a secure process to recreate the nucleotide chain sequence.

2. (Previously presented) The computer-implemented security system of claim 1, wherein the system for outputting further comprises a system for transmitting encrypted coding regions and unencrypted non-coding regions.

3. (Previously presented) The computer-implemented security system of claim 2, wherein the system for transmitting encrypted coding regions and unencrypted non-coding regions includes at least one XML document.

4. (Previously presented) The computer-implemented security system of claim 2, wherein the system for transmitting encrypted coding regions and unencrypted non-coding regions includes web services.

5. (Previously presented) The computer-implemented security system of claim 1, wherein the system for selectively encrypting only the coding regions utilizes cipher block chain encrypting.

6. (Previously presented) The computer-implemented security system of claim 2, further comprising:

a system for receiving the encrypted coding regions and unencrypted non-coding regions;

a system for decrypting the encrypted coding regions; and

a system for regenerating the nucleotide chain from the decrypted coding regions and unencrypted non-coding regions.

7. (Previously presented) The computer-implemented security system of claim 6, wherein the system for receiving the encrypted coding regions and unencrypted non-coding regions comprises a bioinformatics database for receiving nucleotide chain queries.

8. (Currently amended) A method for transmitting a nucleotide chain sequence, comprising:

identifying all coding and non-coding regions in the nucleotide chain sequence;
selectively encrypting only the coding regions identified in the nucleotide chain to generate encrypted coding regions and unencrypted non-coding regions;
transmitting the encrypted coding regions and unencrypted non-coding regions;
receiving the encrypted coding regions and unencrypted non-coding regions;
decrypting the encrypted coding regions;
regenerating the nucleotide chain sequence from the decrypted coding regions and unencrypted non-coding regions; and
outputting the regenerated nucleotide chain sequence.

9. (Canceled)

10. (Currently amended) The method of claim 8, comprising the further step of querying a bioinformatics database with the received nucleotide chain sequence.

11. (Original) The method of claim 8, wherein the encrypted coding regions and unencrypted non-coding regions are transmitted in at least one XML document.

12. (Original) The method of claim 8, wherein the encrypted coding regions and unencrypted non-coding regions are transmitted using web services.

13. (Original) The method of claim 8, wherein the step of selectively encrypting only the coding regions utilizes cipher block chain encrypting.

14. (Currently amended) A program product stored on a recordable medium for encoding a nucleotide chain sequence, comprising:

means for identifying all coding and non-coding regions in the nucleotide chain sequence;

means for selectively encrypting only the coding regions identified in the nucleotide chain sequence; and

means for outputting the encrypted coding regions and the non-encrypted non-coding regions, wherein the encrypted coding regions require decryption by a secure process to recreate the nucleotide chain sequence.

15. (Original) The program product of claim 14, wherein the encrypted coding regions and unencrypted non-coding regions are stored in at least one XML document.

16. (Original) The program product of claim 14, wherein the means for selectively encrypting only the coding regions utilizes cipher block chain encrypting.

17. (Currently amended) A program product stored on a recordable medium for decoding an encoded nucleotide chain, comprising:

means for identifying encrypted coding and unencrypted non-coding regions in the encoded nucleotide chain sequence;

means for selectively decrypting only the coding regions identified in the encoded nucleotide chain sequence;

means for reassembling the coding and non-coding regions to generate a decoded nucleotide chain sequence; and

means for outputting the decoded nucleotide chain sequence.

18. (Original) The program product of claim 17, wherein the coding regions and non-coding regions are stored in at least one XML document.

19. (Original) The program product of claim 17, wherein the means for selectively decrypting only the coding regions utilizes cipher block chain decrypting.

20. (Currently amended) The program product of claim 17, further comprising means for querying a bioinformatics database with the decoded nucleotide chain sequence.